



TITAN VARIO.2 + STOPPER

Ski brake	mm.65	mm.78	mm.85	mm.94
Weight	309 gr			
Downhill angle	2.9°			
Uphill angle	5.8° 8.8° 10.6°			
Heel setting	24 mm			
Material	Ergal - Titanium - Steel Technopolymer			
Release	5-7	7-9	9-11	

BRAND 100% MOHAIR SKINS



ORTLES

Cod.42060 ORTLES CORK HANDLE
Cod.42061 ORTLES CLIP STRAP



ALU' LOCK

Material: Carbon Ø 14 + Carbon reinforcements
Strap: Ortles Clip strap
Handle: Ortles Cork handle
Basket: Ortles basket
Size: customised
Weight: 245 gr.



Cod.42062 TIPS+BASKET ORTLES QC
Cod.42042 BASE AND NUT QC
Cod.42043 BASKET GARA QC
Cod.42044 BASKET TORNADO BIG QC
Cod.42045 ROLLSKI TIP QC



GRAZIE PER AVER SCELTO SKI TRAB

Gli sci contraddistinti dal marchio "made in Bormio" sono garantiti per 3 anni contro i difetti di fabbricazione. La garanzia parte dalla data di acquisto dello sci (fa fede la ricevuta di acquisto). Se riscontrato un difetto di fabbricazione lo sci potrà essere sostituito o riparato a discrezione di SKI TRAB. In ogni caso se ne garantirà il perfetto funzionamento. La garanzia non copre i danni allo sci causati da forti impatti dovuti ad uso non appropriato o da cadute, danni allo sci causati da contatti contro sassi, rocce o altre superfici diverse dalla neve, abrasioni, intaccature e sfilamenti della superficie o dei fianchi e delle estremità. Non copre inoltre danni causati da infiltrazioni d'acqua dovute ad abrasioni sul fianco o da fori attacchi non sigillati, scolorimenti della grafica, danni causati da montaggi impropri o montaggi di attacchi che non utilizzano viti appropriate o attacchi che lacerano la superficie dello sci perché non rispettosi degli standard.

THANK YOU FOR CHOOSING SKI TRAB.

All skis marked with the brand "made in Bormio" are guaranteed against manufacturing faults for 3 years. 3-year warranty from the date of purchase on the sale receipt. If a manufacturing fault is found, the skis can be replaced or repaired at SKI TRAB's discretion. In any case, perfect functioning will be ensured. The warranty does not cover damage to the skis caused by strong impacts due to improper use or falls, damage to the skis resulting from contacts with stones, rocks or any surfaces other than snow, abrasions, cracks/cuts and fraying of the surface or the sidewalls as well as of the tips and tails of the skis. This warranty doesn't also cover damage caused by water infiltration due to abrasions on the sidewall or unsealed ski-binding holes, fading of the graphics, damage resulting from improper mounting or mounting of ski-binding with inappropriate screws or ski-bindings tearing the surface of the skis because not in compliance with Standards.



SKITRAB.COM

SKITRAB

BERNINA




SIZE (CM)	150	157	164	171
WEIGHT (GR)	965	1010	1055 g	1100
RADIUS (MT)	17,50	20,08	21,10	21,10
SURFACE (CM2)	1444	1511	1569	1616
TORSION	CARBON	CARBON	CARBON	CARBON
SIDECUT (MM)	118/88/104	118/88/104	118/87/104	118/85/104

BERNINA cod. 13181

4 LAYER CONTROL

Bernina offers the best downhill performance of the line. It is perfect for demanding skiers with a good level of technical skill, for lighter skiers or for those looking for softer and more manageable skis. The core is made with Liwood air and 14-layer technologies guaranteeing excellent reliability and low weight. Control progressive flex, hiconnect and no shock active vibration control for safe, precise turns. The ideal ski for those looking for equipment that instantly responds to the commands of the skier.



- 1** CONSTRUCTION: CAP QUADRIAXIAL
- 2** PROTECTION SHEET: PA STRONG PROTECTION
- 3** CORE: HARD WOOD-LIGHT WOOD
- 4** FIBERGLASS SUPPORT: BIAxIAL FIBERGLASS
- 5** EDGE: STEEL 52HRC
- 6** TORSION REINFORCEMENTS: CARBON HM
- 7** CAP REINFORCEMENT: CARBON-BASALT
- 8** BASE: SINTERED BLACK BASE
- 9** FINISHING: EDGE RADIAL - TUNING 89°
- 10** BASE FINISHING: MICROSTRUCTURED
- 11** BINDING PLATE/ANTI-TORSIONAL PLATE: MULTI LAYER FIBERGLASS

LIWOOD AIR
DIFFERENTIATED AERO WOOD CORE

LIGHT WOOD
PLACE OF ORIGIN: THE EAST
USE: WOODWORK, SKIS
DENSITY: 270/300 KG M³
COMPRESSIVE STRENGTH MPA 18
CHARACTERISTICS: LIGHTWEIGHT, EASY TO PROCESS



FRAXINUS L. / ASH TREE
PLACE OF ORIGIN: EUROPE
USE: BUILDING INDUSTRY, TOOLS, FUEL
DENSITY: 600/700 KG M³
COMPRESSIVE STRENGTH MPA 30
CHARACTERISTICS: SOLID AND HIGHLY FLEXIBLE

= LIWOOD AIR CORE

ATTIVO

CONTROL FLEX

DUOTAIL

HIBOX

HICONNECT

NOSHOCK

RADIUS CONTROL